

# Front Mount Telescopic

## 5384T

- For trucks with 72" to 84" CA
- Designed for trucks with 25,500 to 33,000 GVWR
- Direct mount pump
- 10 gallon reservoir
- One 5" 3 stage cylinder 84" stroke
- For 9' to 10' body lengths
- 45 to 50 degree dump angle
- 6" longitudinal recommended
- Weight 664 lbs.

### Model 5384T

## 73120T

- For trucks with 108" to 120" CT
- Designed for trucks with 50,000 GVWR
- Direct mount pump
- 26.5 gallon reservoir
- One 7" 3 stage cylinder 120" stroke
- For 14" to 15' body lengths
- 45 to 50 degree dump angle
- 7" longitudinal recommended
- Weight 1018 lbs.

### Model 73120T Class 120

## 63108T

- For trucks with 102" to 114" CT
- Designed for trucks with 33,000 to 50,000 GVWR
- Direct mount pump
- 26.5 gallon reservoir
- One 6" 3 stage cylinder 108" stroke
- For 10" to 13' body lengths
- 45 to 50 degree dump angle
- 7" longitudinal recommended
- Weight 941 lbs.

### Model 63108T Class 100



## 74135T

- For trucks with 132" to 144" CT
- Designed for trucks with 50,000 GVWR
- Direct mount pump
- 26.5 gallon reservoir
- One 7" 4 stage cylinder 135" stroke
- For 16' and 17' body lengths
- 45 to 50 degree dump angle
- 7" longitudinal recommended
- Weight 1045 lbs.

### Model 74135T Class 120

## 63120T

- For trucks with 108" to 120" CT
- Designed for trucks with 50,000 GVWR
- Direct mount pump
- 26.5 gallon reservoir
- One 6" 3 stage cylinder 120" stroke
- For 14' to 15' body lengths
- 45 to 50 degree dump angle
- 7" longitudinal recommended
- Weight 951 lbs.

### Model 63120T Class 110

## 74156T

- For trucks with 156" to 180" CT
- Designed for trucks with 50,000 GVWR
- Direct mount pump
- 26.5 gallon reservoir
- One 7" 4 stage cylinder 156" stroke
- For 18' and 19' body lengths
- 45 to 50 degree dump angle
- 7" longitudinal recommended
- Weight 1085 lbs.

### Model 74156T